



Korean
version



Japan-HQ
Korea
Americas
ASEAN
China
Europe
India
Mexico
Taiwan
Thailand
Turkey

CC-Link IE
CC-Link CC-Link/IT
CC-Link Safety

CC-Link Partner Product

CC-Link 접속 신제품 소개

2021년 8월

CC-Link

CC-Link IE

Belden Hirschmann Industries(Suzhou)Ltd.

A5JSJSA6014-CC-Link IE TSN CAT5e 1000 Mbps Double-Ended Cord set

CC-Link IE TSN CAT5e 1000 Mbps Double-Ended Cord set: male straight transparent RJ45 to male straight transparent RJ45, shielded, LSZH cable, 4 Pairs.



특징

- Cable Design : 4P 26AWG Cat 5e S/FTP LSZH Patch Cable
- Conductor Material : Stranded Bare Copper
- Insulation Material : Polyolefin
- No. of Cores/Pairs (cable) : 4 pairs
- Shielding Type : Each pair with individual foil+overall braid shield
- Shielding Material : Copper alloy
- Outer Jacket Material : LSZH
- Overall Diameter (mm) : Nom. 6.2 mm
- Operational Temperature : -25°C to + 70°C
- Oil resistance : Yes
- Flame Retardant : FT2, IEC60332-1, IEC 60332-3A
- Maximum operating voltage (V) : 30 V
- RoHS Compliant : Yes

사양

항목	내용
통신속도	1Gbps
전송가능거리	
외형치수	
중량	

판매처

제조사	Belden Hirschmann Industries (Suzhou)	http://www.belden.com/

Belden Hirschmann Industries(Suzhou)Ltd.

A5JSJSA6014-CC-Link IE Field CAT5e 1000 Mbps Double-Ended Cord set

CC-Link IE Field CAT5e 1000 Mbps Double-Ended Cord set: male straight transparent RJ45 to male straight transparent RJ45, shielded, LSZH cable, 4 Pairs.



특징

- Cable Design : 4P 26AWG Cat 5e S/FTP LSZH Patch Cable
- Conductor Material : Stranded Bare Copper
- Insulation Material : Polyolefin
- No. of Cores/Pairs (cable) : 4 pairs
- Shielding Type : Each pair with individual foil+overall braid shield
- Shielding Material : Copper alloy
- Outer Jacket Material : LSZH
- Overall Diameter (mm) : Nom. 6.2 mm
- Operational Temperature : -25°C to + 70°C
- Oil resistance : Yes
- Flame Retardant : FT2, IEC60332-1, IEC 60332-3A
- Maximum operating voltage (V) : 30 V
- RoHS Compliant : Yes

사양

항목	내용
통신속도	1Gbps
전송가능거리	
외형치수	
중량	

판매처

제조사	Belden Hirschmann Industries (Suzhou)	http://www.belden.com/

Belden Hirschmann Industries(Suzhou)Ltd.

A5JSJSA6016-CC-Link IE TSN CAT5e 1000 Mbps Double-Ended Cord set

CC-Link IE TSN CAT5e 1000 Mbps Double-Ended Cord set: male straight transparent RJ45 to male straight transparent RJ45, shielded, PVC cable, 4 Pairs.



특징

- Cable Design : 4P 26AWG Cat 5e S/FTP PVC Patch Cable
- Conductor Material : Stranded Bare Copper
- Insulation Material : Polyolefin
- No. of Cores/Pairs (cable) : 4 pairs
- Shielding Type : Each pair with individual foil+overall braid shield
- Shielding Material : Copper alloy
- Outer Jacket Material : PVC
- Overall Diameter (mm) : Nom. 6.2 mm
- Operational Temperature : -25°C to + 70°C
- Oil resistance : Yes
- Flame Retardant : FT2, IEC60332-1, IEC 60332-3A
- Maximum operating voltage (V) : 30 V
- RoHS Compliant : Yes

사양

항목	내용
통신속도	1Gbps
전송가능거리	
외형치수	
중량	

판매처

제조사	Belden Hirschmann Industries (Suzhou)	http://www.belden.com/

Belden Hirschmann Industries(Suzhou)Ltd.

A5JSJSA6016-CC-Link IE Field CAT5e 1000 Mbps Double-Ended Cord set

CC-Link IE Field CAT5e 1000 Mbps Double-Ended Cord set: male straight transparent RJ45 to male straight transparent RJ45, shielded, PVC cable, 4 Pairs.



특징

- Cable Design : 4P 26AWG Cat 5e S/FTP PVC Patch Cable
- Conductor Material : Stranded Bare Copper
- Insulation Material : Polyolefin
- No. of Cores/Pairs (cable) : 4 pairs
- Shielding Type : Each pair with individual foil+overall braid shield
- Shielding Material : Copper alloy
- Outer Jacket Material : PVC
- Overall Diameter (mm) : Nom. 6.2 mm
- Operational Temperature : -25°C to + 70°C
- Oil resistance : Yes
- Flame Retardant : FT2, IEC60332-1, IEC 60332-3A
- Maximum operating voltage (V) : 30 V
- RoHS Compliant : Yes

사양

항목	내용
통신속도	1Gbps
전송가능거리	
외형치수	
중량	

판매처

제조사	Belden Hirschmann Industries (Suzhou)	http://www.belden.com/

Belden Hirschmann Industries(Suzhou)Ltd.

A5JSJSA6038-CC-Link IE TSN CAT5e 1000 Mbps Double-Ended Cord set

CC-Link IE TSN CAT5e 1000 Mbps Double-Ended Cord set: male straight transparent RJ45 to male straight transparent RJ45, shielded, PU cable, 4 Pairs.



특징

- Cable Design : 4P 26AWG Cat 5e S/FTP PVC/PU Patch Cable
- Conductor Material : Stranded Bare Copper
- Insulation Material : Polyolefin
- No. of Cores/Pairs (cable) : 4 pairs
- Shielding Type : Each pair with individual foil+overall braid shield
- Shielding Material : Copper alloy
- Outer Jacket Material : Special compound Polyurethane (UL 758 & UL 1581)
- Overall Diameter (mm) : Nom. 6.2 mm
- Operational Temperature : -25°C to + 70°C
- Oil resistance : Yes
- Flame Retardant : FT2, IEC60332-1, IEC 60332-3A
- Maximum operating voltage (V) : 30 V
- RoHS Compliant : Yes

사양

항목	내용
통신속도	1Gbps
전송가능거리	
외형치수	
중량	

판매처

제조사	Belden Hirschmann Industries (Suzhou)	http://www.belden.com/

Belden Hirschmann Industries(Suzhou)Ltd.

A5JSJSA6038-CC-Link IE Field CAT5e 1000 Mbps Double-Ended Cord set

CC-Link IE Field CAT5e 1000 Mbps Double-Ended Cord set: male straight transparent RJ45 to male straight transparent RJ45, shielded, PU cable, 4 Pairs.



특징

- Cable Design : 4P 26AWG Cat 5e S/FTP PVC/PU Patch Cable
- Conductor Material : Stranded Bare Copper
- Insulation Material : Polyolefin
- No. of Cores/Pairs (cable) : 4 pairs
- Shielding Type : Each pair with individual foil+overall braid shield
- Shielding Material : Copper alloy
- Outer Jacket Material : Special compound Polyurethane (UL 758 & UL 1581)
- Overall Diameter (mm) : Nom. 6.2 mm
- Operational Temperature : -25°C to + 70°C
- Oil resistance : Yes
- Flame Retardant : FT2, IEC60332-1, IEC 60332-3A
- Maximum operating voltage (V) : 30 V
- RoHS Compliant : Yes

사양

항목	내용
통신속도	1Gbps
전송가능거리	
외형치수	
중량	

판매처

제조사	Belden Hirschmann Industries (Suzhou)	http://www.belden.com/

Belden Hirschmann Industries(Suzhou)Ltd.

A5JSJSA6039-CC-Link IE TSN CAT5e 1000 Mbps Double-Ended Cord set

CC-Link IE TSN CAT5e 1000 Mbps Double-Ended Cord set : male straight transparent RJ45 to male straight transparent RJ45, shielded, TPE cable,4 Pairs.



특징

- Cable Design : 4P 26AWG Cat 5e S/FTP TPE Patch Cable
- Conductor Material : Stranded Bare Copper
- Insulation Material : Polyolefin
- No. of Cores/Pairs (cable) : 4 pairs
- Shielding Type : Each pair with individual foil+overall braid shield
- Shielding Material : Copper alloy
- Outer Jacket Material : TPE
- Overall Diameter (mm) : Nom. 6.2 mm
- Operational Temperature : -25°C to + 70°C
- Oil resistance : Yes
- Flame Retardant : FT2, IEC60332-1, IEC 60332-3A
- Maximum operating voltage (V) : 30 V
- RoHS Compliant : Yes

사양

항목	내용
통신속도	1Gbps
전송가능거리	
외형치수	
중량	

판매처

제조사	Belden Hirschmann Industries (Suzhou)	http://www.belden.com/

Belden Hirschmann Industries(Suzhou)Ltd.

A5JSJSA6039-CC-Link IE Field CAT5e 1000 Mbps Double-Ended Cord set

CC-Link IE Field CAT5e 1000 Mbps Double-Ended Cord set : male straight transparent RJ45 to male straight transparent RJ45, shielded, TPE cable,4 Pairs.



특징

- Cable Design : 4P 26AWG Cat 5e S/FTP TPE Patch Cable
- Conductor Material : Stranded Bare Copper
- Insulation Material : Polyolefin
- No. of Cores/Pairs (cable) : 4 pairs
- Shielding Type : Each pair with individual foil+overall braid shield
- Shielding Material : Copper alloy
- Outer Jacket Material : TPE
- Overall Diameter (mm) : Nom. 6.2 mm
- Operational Temperature : -25°C to + 70°C
- Oil resistance : Yes
- Flame Retardant : FT2, IEC60332-1, IEC 60332-3A
- Maximum operating voltage (V) : 30 V
- RoHS Compliant : Yes

사양

항목	내용
통신속도	1Gbps
전송가능거리	
외형치수	
중량	

판매처

제조사	Belden Hirschmann Industries (Suzhou)	http://www.belden.com/

Belden Hirschmann Industries(Suzhou)Ltd.

E7JSJSE6011- CC-Link IE Field CAT6A 10 Gigabit Ethernet double-ended cord set

CC-Link IE Field CAT6A 10 Gigabit Ethernet double-ended cord set, Male straight black RJ45 to male straight black RJ45, shielded, PU black cable, 4 Pairs.



특징

- Cable Design : 4P 26AWG Cat 6 S/FTP PU Cable
- Conductor Material : Stranded Bare Copper
- Insulation Material : Polyolefin
- No. of Cores/Pairs (cable) : 4 pairs
- Shielding Type : Each pair with individual foil shield
- Shielding Material : Copper alloy
- Outer Jacket Material : PU
- Overall Diameter (mm) : Nom. 6.25 mm
- Operational Temperature : -25°C to + 70°C
- Oil resistance : Yes
- Flame Retardant : FT2, IEC60332-1
- Maximum operating voltage (V) : 30 V
- RoHS Compliant : Yes

사양

항목	내용
통신속도	
전송가능거리	
외형치수	
중량	

판매처

제조사	Belden Hirschmann Industries (Suzhou)	http://www.belden.com/

Belden Hirschmann Industries(Suzhou)Ltd.

A7JSJSA6021-CC-Link IE Field CAT6A 10 Gigabit Ethernet double-ended cordset

CC-Link IE Field CAT6A 10 Gbps 10 Gigabit Ethernet double-ended cordset, Male straight transparent RJ45 to male straight transparent RJ45, shielded, PVC cable, 4 Pairs.

특징

- Cable Design : 4P 26AWG Cat 6A S/FTP LSZH Patch Cable
- Conductor Material : Stranded Bare Copper
- Insulation Material : Polyolefin
- No. of Cores/Pairs (cable) : 4 pairs
- Shielding Type : Each pair with individual foil+overall braid shield
- Shielding Material : Copper alloy
- Outer Jacket Material : LSZH
- Overall Diameter (mm) : Nom. 6.2 mm
- Operational Temperature : -25°C to + 70°C
- Oil resistance : Yes
- Flame Retardant : FT2, IEC60332-1
- Maximum operating voltage (V) : 30 V
- RoHS Compliant : Yes

사양

항목	내용
통신속도	
전송가능거리	
외형치수	
중량	

판매처

제조사	Belden Hirschmann Industries (Suzhou)	http://www.belden.com/

Belden Hirschmann Industries(Suzhou)Ltd.

A7JSJSA6023-CC-Link IE Field CAT6A 10 Gigabit Ethernet double-ended cordset

CC-Link IE Field CAT6A 10 Gigabit Ethernet double-ended cordset, Male straight black RJ45 to male straight black RJ45, shielded, PVC blue cable, 4 Pairs.



특징

- Cable Design : 4P 26AWG Cat 6A S/FTP PVC Patch Cable
- Conductor Material : Stranded Bare Copper
- Insulation Material : Polyolefin
- No. of Cores/Pairs (cable) : 4 pairs
- Shielding Type : Each pair with individual foil+overall braid shield
- Shielding Material : Copper alloy
- Outer Jacket Material : PVC
- Overall Diameter (mm) : Nom. 6.2 mm
- Operational Temperature : -25°C to + 70°C
- Flame Retardant : FT2, IEC60332-1
- Maximum operating voltage (V) : 30 V
- RoHS Compliant : Yes

사양

항목	내용
통신속도	
전송가능거리	
외형치수	
중량	

판매처

제조사	Belden Hirschmann Industries (Suzhou)	http://www.belden.com/

Belden Hirschmann Industries(Suzhou)Ltd.

E5JSJSC9055-CC-Link IE TSN CAT5e 1000 Mbps Double-Ended Cord set

CC-Link IE TSN CAT5e 1000 Mbps Double-Ended Cord set: male straight black RJ45 to male straight black RJ45, shielded, PVC blue jacket, 4 Pairs.



특징

- Cable Design : 4P 24AWG Cat 5e SF/UTP PVC Patch Cable
- Conductor Material : Solid Bare Copper
- Insulation Material : Polyolefin
- No. of Cores/Pairs (cable) : 4 pairs
- Shielding Type : Tinned Copper Braid
- Shielding Material : Copper alloy
- Outer Jacket Material : PVC
- Overall Diameter (mm) : Nom. 6.70 mm
- Operational Temperature : -25°C to + 75°C
- Oil resistance : No
- Flame Retardant : VW-1
- Maximum operating voltage (V) : 30 V
- RoHS Compliant : Yes

사양

항목	내용
통신속도	1Gbps
전송가능거리	
외형치수	
중량	

판매처

제조사	Belden Hirschmann Industries (Suzhou)	http://www.belden.com/

Belden Hirschmann Industries(Suzhou)Ltd.

E5JSJSC9055-CC-Link IE Field CAT5e 1000 Mbps Double-Ended Cord set

CC-Link IE Field CAT5e 1000 Mbps Double-Ended Cord set: male straight black RJ45 to male straight black RJ45, shielded, PVC blue jacket, 4 Pairs.



특징

- Cable Design : 4P 24AWG Cat 5e SF/UTP PVC Patch Cable
- Conductor Material : Solid Bare Copper
- Insulation Material : Polyolefin
- No. of Cores/Pairs (cable) : 4 pairs
- Shielding Type : Tinned Copper Braid
- Shielding Material : Copper alloy
- Outer Jacket Material : PVC
- Overall Diameter (mm) : Nom. 6.70 mm
- Operational Temperature : -25°C to + 75°C
- Oil resistance : No
- Flame Retardant : VW-1
- Maximum operating voltage (V) : 30 V
- RoHS Compliant : Yes

사양

항목	내용
통신속도	1Gbps
전송가능거리	
외형치수	
중량	

판매처

제조사	Belden Hirschmann Industries (Suzhou)	http://www.belden.com/