



Korean
version



Japan-HQ
Korea
Americas
ASEAN
China
Europe
India
Mexico
Taiwan
Thailand
Turkey

CC-Link IE⁺
CC-Link CC-Link/LT
CC-Link Safety

CC-Link Partner Product
CC-Link Family 접속 신제품 소개
2022년 2월

CC-Link **IE TSN**

CC-Link

Metal Work Spa

EB80 series

Electro-pneumatic system, a single assembly can combine solenoid valves and digital or analogue input or output signal control modules



특징

- The possible combinations are endless, the range of the Power supply is from 12 -10% to 24 +30%.

사양

항목	내용
국종	슬레이브국
점유국수	1-4
프로토콜버전	2

판매처

제조사	Metal Work Spa	https://www.metalwork.it/

SILA Embedded Solutions GmbH

CC-Link IE TSN Remote Station SDK

CC-Link IE TSN software development kit for remote station provides a portable C source code with sample applications for Linux. A unified porting layer allows easy adaption of the stack to customer specific hardware. The SDK is self-contained and no further costs are involved for development of a CC-Link IE TSN remote station.



특징

- Delivered as C source code with demos already supporting iMX6.
- The stack is TSN ready and uses hardware MAC support for 802.1AS and 1588v2 if available.
- A Software 802.1Qbv implementation is available supporting a wide range of microprocessors.
- Demos are fully run-able, complete with OS, TCP/IP stack, documentation and samples to reduce development time.
- Professional support for the whole product development cycle from experts in embedded systems design.

사양

항목	내용
인증클래스	A
통신속도	1Gbps,100Mbps

판매처

제조사	SILA Embedded Solutions	https://www.embedded-solutions.at/en/

Belden Hirschmann Industries (Suzhou) Ltd.

IE-M12XM-M12XM-xxM CC-Link IE TSN Category 5e 1000 Mbps Double-Ended Cord set.

CC-Link IE TSN Category 5e 1000 Mbps Double-Ended Cord set: Male straight X-coded black M12 standard to male straight X-coded black M12 standard, shielded, PVC orange cable, 8 wires.



특징

- Cable Design: 4P CAT5e SF/UTP/ PE/OS/OBS/PVC Fixed LAN Cable
- CC-Link IE TSN Reference Number: NRT-IT-00033
- Conductor Material: Solid Bare Copper
- Insulation Material: Polyolefin
- No. of Cores/Pairs (cable): 4 pairs
- Shielding Type: Al-Mylar + Braid
- Shielding Material: Tinned Copper
- Outer Jacket Material: PVC
- Overall Diameter (mm): Nom. 6.70 mm
- Operational Temperature: -30°C to + 75°C
- Oil resistance: Yes
- UV/Sunlight resistance: Yes
- Flame Retardant: IEC 60332-1, UL 444 (CM)
- Maximum operating voltage (V): 300 V
- Characteristics Impedance (MΩ.km): 100 ± 15 MΩ.km
- RoHS Compliant: Yes
- For Connector Type: M12 Standard

사양

항목	내용
통신속도	1Gbps
전송가능 거리	
케이블 외경	
중량	

판매처

제조사	Belden Hirschmann	http://www.belden.com/

Belden Hirschmann Industries (Suzhou) Ltd.

IE-M12XM-M12XM-xxM CC-Link IE Field Category 5e 1000 Mbps Double-Ended Cord set.

CC-Link IE Field Category 5e 1000 Mbps Double-Ended Cord set: Male straight X-coded black M12 standard to male straight X-coded black M12 standard, shielded, PVC orange cable, 8 wires.



특징

- Cable Design: 4P CAT5e SF/UTP/ PE/OS/OBS/PVC Fixed LAN Cable
- CC-Link IE Field Reference Number: NRT-IF-00034
- Conductor Material: Solid Bare Copper
- Insulation Material: Polyolefin
- No. of Cores/Pairs (cable): 4 pairs
- Shielding Type: Al-Mylar + Braid
- Shielding Material: Tinned Copper
- Outer Jacket Material: PVC
- Overall Diameter (mm): Nom. 6.70 mm
- Operational Temperature: -30°C to + 75°C
- Oil resistance: Yes
- UV/Sunlight resistance: Yes
- Flame Retardant: IEC 60332-1, UL 444 (CM)
- Maximum operating voltage (V): 300 V
- Characteristics Impedance (MΩ.km): 100 ± 15 MΩ.km
- RoHS Compliant: Yes
- For Connector Type: M12 Standard

사양

항목	내용
통신속도	1Gbps
전송가능 거리	
케이블 외경	
중량	

판매처

제조사	Belden Hirschmann	http://www.belden.com/

Belden Hirschmann Industries (Suzhou) Ltd.

IE-M12XM-RJ45-xxM CC-Link IE TSN Category 5e 1000 Mbps Double-Ended Cord set.

CC-Link IE TSN Category 5e 1000 Mbps Double-Ended Cord set: Male straight X-coded black M12 standard to male straight black RJ45, shielded, PVC orange cable, 8 wires.



특징

- Cable Design: 4P CAT5e PE/OS/OBS/PVC Fixed LAN Cable
- CC-Link IE TSN Reference Number: NRT-IT-00038
- Conductor Material: Solid Bare Copper
- Insulation Material: Polyolefin
- No. of Cores/Pairs (cable): 4 pairs
- Shielding Type: Al-Mylar + Braid
- Shielding Material: Tinned Copper
- Outer Jacket Material: PVC
- Overall Diameter (mm): Nom. 6.70 mm
- Operational Temperature: -30°C to + 75°C
- Oil resistance: Yes
- UV/Sunlight resistance: Yes
- Flame Retardant: IEC 60332-1, UL 444 (CM)
- Maximum operating voltage (V): 300 V
- Characteristics Impedance (MΩ.km): 100 ± 15 MΩ.km
- RoHS Compliant: Yes
- For Connector Type: M12 Standard / RJ45 Male

사양

항목	내용
통신속도	1Gbps
전송가능 거리	
케이블 외경	
중량	

판매처

제조사	Belden Hirschmann	http://www.belden.com/

Belden Hirschmann Industries (Suzhou) Ltd.

IE-M12XM-RJ45-xxM CC-Link IE Field Category 5e 1000 Mbps Double-Ended Cord set.

CC-Link IE Field Category 5e 1000 Mbps Double-Ended Cord set: Male straight X-coded black M12 standard to male straight black RJ45, shielded, PVC orange cable, 8 wires.



특징

- Cable Design: 4P CAT5e PE/OS/OBS/PVC Fixed LAN Cable
- CC-Link IE Field Reference Number: NRT-IF-00041
- Conductor Material: Solid Bare Copper
- Insulation Material: Polyolefin
- No. of Cores/Pairs (cable): 4 pairs
- Shielding Type: Al-Mylar + Braid
- Shielding Material: Tinned Copper
- Outer Jacket Material: PVC
- Overall Diameter (mm): Nom. 6.70 mm
- Operational Temperature: -30°C to + 75°C
- Oil resistance: Yes
- UV/Sunlight resistance: Yes
- Flame Retardant: IEC 60332-1, UL 444 (CM)
- Maximum operating voltage (V): 300 V
- Characteristics Impedance (MΩ.km): 100 ± 15 MΩ.km
- RoHS Compliant: Yes
- For Connector Type: M12 Standard / RJ45 Male

사양

항목	내용
통신속도	1Gbps
전송가능 거리	
케이블 외경	
중량	

판매처

제조사	Belden Hirschmann	http://www.belden.com/

Belden Hirschmann Industries (Suzhou) Ltd.

IEM-M12XM-M12XM-xxM CC-Link IE TSN Category 5e 1000 Mbps Double-Ended Cord set.

CC-Link IE TSN Category 5e 1000 Mbps Double-Ended Cord set: Male straight X-coded black M12 standard to male straight X-coded black M12 standard, shielded, PVC orange cable, 8 wires.



특징

- Cable Design: 4P CAT5e SF/UTP MOV PVC Cable
- CC-Link IE TSN Reference Number: NRT-IT-00041
- Conductor Material: Copper alloy
- Insulation Material: FEP
- No. of Cores/Pairs (cable): 4 pairs
- Shielding Type: Overall Foil Shield with Tinned Tinsel wire Braid
- Shielding Material: Tinned Copper
- Outer Jacket Material: PVC
- Overall Diameter (mm): Nom. 6.90 mm
- Operational Temperature: -20°C to + 80°C
- Flame Retardant: VW-1
- Reverse Bending test: 20 million (R = 40 mm)
- Torsion test: 20 million (+/-180°, L = 300 mm)
- Trailing chain test: 20 million (R = 38 mm)
- Maximum operating voltage (V): 30 V
- Characteristics Impedance (Ω @ 1-100MHz): $100 \pm 15 \Omega$
- RoHS Compliant: Yes
- For Connector Type: M12 Standard

사양

항목	내용
통신속도	1Gbps
전송가능 거리	
케이블 외경	
중량	

판매처

제조사	Belden Hirschmann	http://www.belden.com/

Belden Hirschmann Industries (Suzhou) Ltd.

IEM-M12XM-M12XM-xxM CC-Link IE Field Category 5e 1000 Mbps Double-Ended Cord set.

CC-Link IE Field Category 5e 1000 Mbps Double-Ended Cord set: Male straight X-coded black M12 standard to male straight X-coded black M12 standard, shielded, PVC orange cable, 8 wires.



특징

- Cable Design: 4P CAT5e SF/UTP MOV PVC Cable
- CC-Link IE Field Reference Number: NRT-IF-00044
- Conductor Material: Copper alloy
- Insulation Material: FEP
- No. of Cores/Pairs (cable): 4 pairs
- Shielding Type: Overall Foil Shield with Tinned Tinsel wire Braid
- Shielding Material: Tinned Copper
- Outer Jacket Material: PVC
- Overall Diameter (mm): Nom. 6.90 mm
- Operational Temperature: -20°C to + 80°C
- Flame Retardant: VW-1
- Reverse Bending test: 20 million (R = 40 mm)
- Torsion test: 20 million (+/-180°, L = 300 mm)
- Trailing chain test: 20 million (R = 38 mm)
- Maximum operating voltage (V): 30 V
- Characteristics Impedance (Ω @ 1-100MHz): $100 \pm 15 \Omega$
- RoHS Compliant: Yes
- For Connector Type: M12 Standard

사양

항목	내용
통신속도	1Gbps
전송가능 거리	
케이블 외경	
중량	

판매처

제조사	Belden Hirschmann	http://www.belden.com/

Belden Hirschmann Industries (Suzhou) Ltd.

IEM-M12XM-RJ45-xxM CC-Link IE TSN Category 5e 1000 Mbps Double-Ended Cord set.

CC-Link IE TSN Category 5e 1000 Mbps Double-Ended Cord set: Male straight X-coded black M12 standard to male straight black RJ45, shielded, PVC orange cable, 8 wires.



특징

- Cable Design: 4P CAT5e SF/UTP MOV PVC Cable
- CC-Link IE TSN Reference Number: NRT-IT-00042
- Conductor Material: Copper alloy
- Insulation Material: FEP
- No. of Cores/Pairs (cable): 4 pairs
- Shielding Type: Overall Foil Shield with Tinned Tinsel wire Braid
- Shielding Material: Tinned Tinsel braid
- Outer Jacket Material: PVC
- Overall Diameter (mm): Nom. 6.90 mm
- Operational Temperature: -20°C to + 80°C
- Flame Retardant: VW-1
- Reverse Bending test: 20 million (R = 40 mm)
- Torsion test: 20 million (+/-180°, L = 300 mm)
- Trailing chain test: 20 million (R = 38 mm)
- Maximum operating voltage (V): 30 V
- Characteristics Impedance (Ω @ 1-100MHz): $100 \pm 15 \Omega$
- RoHS Compliant: Yes
- For Connector Type: M12 Standard / RJ45 Male

사양

항목	내용
통신속도	1Gbps
전송가능 거리	
케이블 외경	
중량	

판매처

제조사	Belden Hirschmann	http://www.belden.com/

Belden Hirschmann Industries (Suzhou) Ltd.

IEM-M12XM-RJ45-xxM CC-Link IE Field Category 5e 1000 Mbps Double-Ended Cord set.

CC-Link IE Field Category 5e 1000 Mbps Double-Ended Cord set: Male straight X-coded black M12 standard to male straight black RJ45, shielded, PVC orange cable, 8 wires.



특징

- Cable Design: 4P CAT5e SF/UTP MOV PVC Cable
- CC-Link IE Field Reference Number: NRT-IF-00045
- Conductor Material: Copper alloy
- Insulation Material: FEP
- No. of Cores/Pairs (cable): 4 pairs
- Shielding Type: Overall Foil Shield with Tinned Tinsel wire Braid
- Shielding Material: Tinned Tinsel braid
- Outer Jacket Material: PVC
- Overall Diameter (mm): Nom. 6.90 mm
- Operational Temperature: -20°C to + 80°C
- Flame Retardant: VW-1
- Reverse Bending test: 20 million (R = 40 mm)
- Torsion test: 20 million (+/-180°, L = 300 mm)
- Trailing chain test: 20 million (R = 38 mm)
- Maximum operating voltage (V): 30 V
- Characteristics Impedance (Ω @ 1-100MHz): $100 \pm 15 \Omega$
- RoHS Compliant: Yes
- For Connector Type: M12 Standard / RJ45 Male

사양

항목	내용
통신속도	1Gbps
전송가능 거리	
케이블 외경	
중량	

판매처

제조사	Belden Hirschmann	http://www.belden.com/

Belden Hirschmann Industries (Suzhou) Ltd.

IEO-M12XM-M12XM-xxM CC-Link IE TSN Category 5e 1000 Mbps Double-Ended Cord set.

CC-Link IE TSN Category 5e 1000 Mbps Double-Ended Cord set: Male straight X-coded black M12 standard to male straight X-coded black M12 standard, shielded, LLDPE black cable, 8 wires.



특징

- Cable Design: 4P CAT5e SF/UTP/ PE/OS/OBS/PE Outdoor LAN Cable
- CC-Link IE TSN Reference Number: NRT-IT-00039
- Conductor Material: Solid Bare Copper
- Insulation Material: Polyolefin
- No. of Cores/Pairs (cable): 4 pairs
- Shielding Type: Al-Mylar + Braid
- Shielding Material: Tinned Copper
- Outer Jacket Material: LLDPE
- Overall Diameter (mm): Nom. 6.80 mm
- Operational Temperature: -30°C to + 80°C
- Oil Resistance: Yes
- UV/Sunlight Resistance: Yes
- Maximum operating voltage (V): 300 V
- Characteristics Impedance (Ω @ 1-100MHz): $100 \pm 15 \Omega$
- RoHS Compliant: Yes
- For Connector Type: M12 Standard

사양

항목	내용
통신속도	1Gbps
전송가능 거리	
케이블 외경	
중량	

판매처

제조사	Belden Hirschmann	http://www.belden.com/

Belden Hirschmann Industries (Suzhou) Ltd.

IEO-M12XM-M12XM-xxM CC-Link IE Field Category 5e 1000 Mbps Double-Ended Cord set.

CC-Link IE Field Category 5e 1000 Mbps Double-Ended Cord set: Male straight X-coded black M12 standard to male straight X-coded black M12 standard, shielded, LLDPE black cable, 8 wires.



특징

- Cable Design: 4P CAT5e SF/UTP/ PE/OS/OBS/PE Outdoor LAN Cable
- CC-Link IE Field Reference Number: NRT-IF-00042
- Conductor Material: Solid Bare Copper
- Insulation Material: Polyolefin
- No. of Cores/Pairs (cable): 4 pairs
- Shielding Type: Al-Mylar + Braid
- Shielding Material: Tinned Copper
- Outer Jacket Material: LLDPE
- Overall Diameter (mm): Nom. 6.80 mm
- Operational Temperature: -30°C to + 80°C
- Oil Resistance: Yes
- UV/Sunlight Resistance: Yes
- Maximum operating voltage (V): 300 V
- Characteristics Impedance (Ω @ 1-100MHz): $100 \pm 15 \Omega$
- RoHS Compliant: Yes
- For Connector Type: M12 Standard

사양

항목	내용
통신속도	1Gbps
전송가능 거리	
케이블 외경	
중량	

판매처

제조사	Belden Hirschmann	http://www.belden.com/

Belden Hirschmann Industries (Suzhou) Ltd.

IEO-M12XM-RJ45-xxM CC-Link IE TSN Category 5e 1000 Mbps Double-Ended Cord set.

CC-Link IE TSN Category 5e 1000 Mbps Double-Ended Cord set: Male straight X-coded black M12 standard to male straight black RJ45, shielded, LLDPE black cable, 8 wires.



특징

- Cable Design: 4P CAT5e SF/UTP/ PE/OS/OBS/PE Outdoor LAN Cable
- CC-Link IE TSN Reference Number: NRT-IT-00040
- Conductor Material: Solid Bare Copper
- Insulation Material: Polyolefin
- No. of Cores/Pairs (cable): 4 pairs
- Shielding Type: Al-Mylar + Braid
- Shielding Material: Tinned Copper
- Outer Jacket Material: LLDPE
- Overall Diameter (mm): Nom. 6.80 mm
- Operational Temperature: -30°C to + 80°C
- Oil Resistance: Yes
- UV/Sunlight Resistance: Yes
- Maximum operating voltage (V): 300 V
- Characteristics Impedance (Ω @ 1-100MHz): $100 \pm 15 \Omega$
- RoHS Compliant: Yes
- For Connector Type: M12 Standard / RJ45 Male

사양

항목	내용
통신속도	1Gbps
전송가능 거리	
케이블 외경	
중량	

판매처

제조사	Belden Hirschmann	http://www.belden.com/

Belden Hirschmann Industries (Suzhou) Ltd.

IEO-M12XM-RJ45-xxM CC-Link IE Field Category 5e 1000 Mbps Double-Ended Cord set.

CC-Link IE Field Category 5e 1000 Mbps Double-Ended Cord set: Male straight X-coded black M12 standard to male straight black RJ45, shielded, LLDPE black cable, 8 wires.



특징

- Cable Design: 4P CAT5e SF/UTP/ PE/OS/OBS/PE Outdoor LAN Cable
- CC-Link IE Field Reference Number: NRT-IF-00043
- Conductor Material: Solid Bare Copper
- Insulation Material: Polyolefin
- No. of Cores/Pairs (cable): 4 pairs
- Shielding Type: Al-Mylar + Braid
- Shielding Material: Tinned Copper
- Outer Jacket Material: LLDPE
- Overall Diameter (mm): Nom. 6.80 mm
- Operational Temperature: -30°C to + 80°C
- Oil Resistance: Yes
- UV/Sunlight Resistance: Yes
- Maximum operating voltage (V): 300 V
- Characteristics Impedance (Ω @ 1-100MHz): $100 \pm 15 \Omega$
- RoHS Compliant: Yes
- For Connector Type: M12 Standard / RJ45 Male

사양

항목	내용
통신속도	1Gbps
전송가능 거리	
케이블 외경	
중량	

판매처

제조사	Belden Hirschmann	http://www.belden.com/

Belden Hirschmann Industries (Suzhou) Ltd.

RSTS-8X-RSTS 8X-6612 CC-Link IE TSN Category 5e 1000 Mbps Double-Ended Cord set.

CC-Link IE TSN Category 5e 1000 Mbps Double-Ended Cord set: Male straight X-coded black M12 standard to male straight X-coded black M12 standard, shielded, PVC orange cable, 8 wires.



특징

- Cable Design: 4P CAT5e SF/UTP/ PE/OS/OBS/ PVC Fixed LAN Cable
- CC-Link IE TSN Reference Number: NRT-IT-00037
- Conductor Material: Solid Bare Copper
- Insulation Material: Polyolefin
- No. of Cores/Pairs (cable): 4 pairs
- Shielding Type: Al-Mylar + Braid
- Shielding Material: Tinned Copper
- Outer Jacket Material: PVC
- Overall Diameter (mm): Nom. 6.70 mm
- Operational Temperature: -30°C to + 75°C
- Oil Resistance: Yes
- UV/Sunlight Resistance: Yes
- Flame Retardant: IEC 60332-1, UL 444 (CM)
- Maximum operating voltage (V): 300 V
- Characteristics Impedance (Ω @ 1-100MHz): $100 \pm 15 \Omega$
- RoHS Compliant: Yes
- For Connector Type: M12 Standard

사양

항목	내용
통신속도	1Gbps
전송가능 거리	
케이블 외경	
중량	

판매처

제조사	Belden Hirschmann	http://www.belden.com/

Belden Hirschmann Industries (Suzhou) Ltd.

RSTS-8X-RSTS 8X-6612 CC-Link IE Field Category 5e 1000 Mbps Double-Ended Cord set.

CC-Link IE Field Category 5e 1000 Mbps Double-Ended Cord set: Male straight X-coded black M12 standard to male straight X-coded black M12 standard, shielded, PVC orange cable, 8 wires.



특징

- Cable Design: 4P CAT5e SF/UTP/ PE/OS/OBS/ PVC Fixed LAN Cable
- CC-Link IE Field Reference Number: NRT-IF-00040
- Conductor Material: Solid Bare Copper
- Insulation Material: Polyolefin
- No. of Cores/Pairs (cable): 4 pairs
- Shielding Type: Al-Mylar + Braid
- Shielding Material: Tinned Copper
- Outer Jacket Material: PVC
- Overall Diameter (mm): Nom. 6.70 mm
- Operational Temperature: -30°C to + 75°C
- Oil Resistance: Yes
- UV/Sunlight Resistance: Yes
- Flame Retardant: IEC 60332-1, UL 444 (CM)
- Maximum operating voltage (V): 300 V
- Characteristics Impedance (Ω @ 1-100MHz): $100 \pm 15 \Omega$
- RoHS Compliant: Yes
- For Connector Type: M12 Standard

사양

항목	내용
통신속도	1Gbps
전송가능 거리	
케이블 외경	
중량	

판매처

제조사	Belden Hirschmann	http://www.belden.com/

Belden Hirschmann Industries (Suzhou) Ltd.

IE-RJ45-RJ45-xxM CC-Link IE TSN Category 5e 1000 Mbps Double-Ended Cord set

CC-Link IE TSN Category 5e 1000 Mbps Double-Ended Cord set: Male straight black RJ45 to male straight black RJ45, shielded, PVC orange cable, 8 wires.



특징

- Cable Design: 4P CAT5e SF/UTP/ PE/OS/OBS/ PVC Fixed LAN Cable
- CC-Link IE TSN Reference Number: NRT-IT-00026
- Conductor Material: Solid Bare Copper
- Insulation Material: Polyolefin
- No. of Cores/Pairs (cable): 4 pairs
- Shielding Type: Al-Mylar + Braid
- Shielding Material: Tinned Copper
- Outer Jacket Material: PVC
- Overall Diameter (mm): Nom. 6.70 mm
- Operational Temperature: -30°C to + 75°C
- Oil Resistance: Yes
- Flame Retardant: IEC 60332-1, UL 444 (CM)
- Maximum operating voltage (V): 300 V
- RoHS Compliant: Yes
- For Connector Type: RJ45 Male

사양

항목	내용
통신속도	1Gbps
전송가능 거리	
케이블 외경	
중량	

판매처

제조사	Belden Hirschmann	http://www.belden.com/

Belden Hirschmann Industries (Suzhou) Ltd.

IE-RJ45-RJ45-xxM CC-Link IE Field Category 5e 1000 Mbps Double-Ended Cord set

CC-Link IE Field Category 5e 1000 Mbps Double-Ended Cord set: Male straight black RJ45 to male straight black RJ45, shielded, PVC orange cable, 8 wires.



특징

- Cable Design: 4P CAT5e SF/UTP/ PE/OS/OBS/ PVC Fixed LAN Cable
- CC-Link IE Field Reference Number: NRT-IF-00028
- Conductor Material: Solid Bare Copper
- Insulation Material: Polyolefin
- No. of Cores/Pairs (cable): 4 pairs
- Shielding Type: Al-Mylar + Braid
- Shielding Material: Tinned Copper
- Outer Jacket Material: PVC
- Overall Diameter (mm): Nom. 6.70 mm
- Operational Temperature: -30°C to + 75°C
- Oil Resistance: Yes
- Flame Retardant: IEC 60332-1, UL 444 (CM)
- Maximum operating voltage (V): 300 V
- RoHS Compliant: Yes
- For Connector Type: RJ45 Male

사양

항목	내용
통신속도	1Gbps
전송가능 거리	
케이블 외경	
중량	

판매처

제조사	Belden Hirschmann	http://www.belden.com/

Belden Hirschmann Industries (Suzhou) Ltd.

IEM-RJ45-RJ45-xxM CC-Link IE TSN Category 5e 1000 Mbps Double-Ended Cord set

CC-Link IE TSN Category 5e 1000 Mbps Double-Ended Cord set: Male straight black RJ45 to male straight black RJ45, shielded, PVC orange cable, 8 wires.



특징

- Cable Design: 4P CAT5e SF/UTP PVC Cable
- Conductor Material: Copper alloy
- Insulation Material: FEP
- No. of Cores/Pairs (cable): 4 pairs
- Shielding Type: Overall Foil Shield with Tinned wire Braid
- Shielding Material: Tinned Tinsel Braid
- Outer Jacket Material: PVC
- Overall Diameter (mm): Nom. 6.90 mm
- Operational Temperature: -20°C to + 80°C
- Flame Retardant: VW-1
- Reverse Bending Test: 20 million (R=40 mm)
- Torsion Test: 20 million (+/- 180°, L=300 mm)
- Trailing Chain Test: 20 million (R=38 mm)
- Maximum operating voltage (V): 30 V
- Characteristics Impedance: 100 ± 15 Ohms
- RoHS Compliant: Yes
- For Connector Type: RJ45 Male

사양

항목	내용
통신속도	1Gbps
전송가능 거리	
케이블 외경	
중량	

판매처

제조사	Belden Hirschmann	http://www.belden.com/

Belden Hirschmann Industries (Suzhou) Ltd.

IEM-RJ45-RJ45-xxM CC-Link IE Field Category 5e 1000 Mbps Double-Ended Cord set

CC-Link IE Field Category 5e 1000 Mbps Double-Ended Cord set: Male straight black RJ45 to male straight black RJ45, shielded, PVC orange cable, 8 wires.



특징

- Cable Design: 4P CAT5e SF/UTP PVC Cable
- Conductor Material: Copper alloy
- Insulation Material: FEP
- No. of Cores/Pairs (cable): 4 pairs
- Shielding Type: Overall Foil Shield with Tinned wire Braid
- Shielding Material: Tinned Tinsel Braid
- Outer Jacket Material: PVC
- Overall Diameter (mm): Nom. 6.90 mm
- Operational Temperature: -20°C to + 80°C
- Flame Retardant: VW-1
- Reverse Bending Test: 20 million (R=40 mm)
- Torsion Test: 20 million (+/- 180°, L=300 mm)
- Trailing Chain Test: 20 million (R=38 mm)
- Maximum operating voltage (V): 30 V
- Characteristics Impedance: 100 ± 15 Ohms
- RoHS Compliant: Yes
- For Connector Type: RJ45 Male

사양

항목	내용
통신속도	1Gbps
전송가능 거리	
케이블 외경	
중량	

판매처

제조사	Belden Hirschmann	http://www.belden.com/